RU

# ПЕЧИ РОТАЦИОННЫЕ

## СЕРИЯ G




Компактные размеры, надежная структура, улучшенная конструкция и широкая функциональность одновременно. Ротационные печи Apach Bakery Line серии G были специально проверены на тяжелые непрерывные циклы выпечки и предназначены как для небольших и ремесленных, так и для промышленных пекарен.

## СТАНДАРТНОЕ ОБОРУДОВАНИЕ

- Версия TS: многофазная панель TOUCH SCREEN с 7 дюймовым TFT, 99 программ с изображениями товаров и USB портом, автоматически программируемый клапан
- Версия DP: цифровая панель управления с 30 сохраняемыми программами, ЖК-экраном и светодиодным дисплеем, программируемая система зажигания, двухскоростной вентилятор
- Версия EMP: электромеханическая панель управления
- Вращение с помощью крюка
- Пониженная скорость обдува для деликатной продукции
- Защита уплотнителей для лучшей теплоизоляции и более длительного срока службы
- Козырек с вытяжкой пара
- Дверь из нержавеющей стали с двойным остеклением и системой открывания на 180°
- Клапан предельного давления в камере
- Облегченная система закрытия дверей, не требующая значительных физических усилий
- Высокопроизводительный парогенератор с коротким временем восстановления
- Доступ к горелке или ТЭНам с левой стороны
- Доступна в электрической или газовой версии (для газовой, LPG или газовой/дизельной горелки)
- Ручка двери выполнена из стали с пониженной теплопроводимостью; внутренняя ручка для безопасности
- Высококачественная термоизоляция за счет использования панелей из высокоплотной минеральной ваты
- Внутренние углы в камере закруглены для легкости и безопасности очистки
- Камера печи, козырек и фронтальная отделка полностью из нержавеющей стали

## ОПЦИИ / АКСЕССУАРЫ

- Возможность установки печей в линию (доступ для обслуживания сзади)
- Платформа (только для G68)
- Автоматический подъем крюка (только для G68)
- Доступ к горелке или ТЭНам с правой стороны
- Усиленные ТЭНы для электрических печей для интенсивного использования
- Панель на козырьке, показывающая время до конца цикла и температуру в камере

## ПРЕИМУЩЕСТВА

- Надежная структура
- Улучшенная конструкция и функциональность
- Оптимальное энергопотребление
- Полный набор опций, необходимых для выпечки любого типа продукта
- Современный и технологичный дизайн

| КОМПЛЕКТАЦИЯ | | | |
|---|---|---|---|
| EMP | DP | TS | |
| ✘ | ✘ | ✓ | Многофазная панель touch screen с 7 дюймовым TFT, 99 программ с изображениями товаров и USB - портом, автоматически программируемый клапан |
| ✘ | ✓ | ✘ | Цифровая панель управления с ЖК-экраном и светодиодным дисплеем, 30 сохраняемых программ |
| ✓ | ✘ | ✘ | Электромеханическая панель управления |
| ✓ | ✓ | ✓ | Пониженная скорость для деликатных продуктов |
| ✓ | ✓ | ✓ | Система вращения при помощи крюка |
| ✓ | ✓ | ✓ | Козырек с вытяжкой пара |
| ✓ | ✓ | ✓ | Дверь с двойным остеклением с открытием на 180˚ |
| ✓ | ✓ | ✓ | Теплоизоляция наружных панелей из нержавеющей стали с использованием панелей из высокоплотной минеральной ваты |
| ✓ | ✓ | ✓ | Внешние панели из нержавеющей стали |
| ✓ | ✓ | ✓ | Запатентованный парогенератор для массивного производства пара с минимальным временем восстановления |
| ✘ | ✓ | ✓ | Автоматическая заслонка пароудаления |
| ✓ | ✘ | ✘ | Ручная заслонка пароудаления |
| ✓ | ✓ | ✓ | Внешний электрошкаф (размещается сзади, сверху или на стене) |
| ✓ | ✓ | ✓ | Печь поставляется в разобранном виде (по запросу в 2 или 3 модулях или в полной сборке) |

✓ По умолчанию

✘ Опция

МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 40X60)
ЭЛЕКТРИЧЕСКИЕ

| **Модель** | **Версия** | **Панель управления** | **Тип сборки** | **Габариты** | | | **Вес** | **Мощность** | **Среднее потребление** |
|---|---|---|---|---|---|---|---|---|---|
| | | | | **д** | **ш** | **в** | | | |
| | | | | **мм** | **мм** | **мм** | **кг** | **кВт** | **кВт/ч** |
| G46E TS | Премиум | Touch screen | Полный разбор | 1000 | 1420 | 2340 | 650 | 24+1,5 | 18 |
| G46E TS2M | | Touch screen | 2 модуля | | | | | | |
| G46E TSTA | | Touch screen | Полная сборка | | | | | | |
| G46E DP | | Цифровая | Полный разбор | | | | | | |
| G46E DP2M | | Цифровая | 2 модуля | | | | | | |
| G46E DPTA | | Цифровая | Полная сборка | | | | | | |
| G46E EMP | Базовая | Электромеханическая | Полный разбор | | | | | | |
| G46E EMPTA | | Электромеханическая | Полная сборка | | | | | | |

| МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 40X60)<br>ГАЗОВЫЕ | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Модель** | **Версия** | **Панель управления** | **Тип сборки** | **Габариты** | | | **Вес** | **Мощность** | **Среднее потребление** |
| | | | | **д** | **ш** | **в** | | | |
| | | | | **мм** | **мм** | **мм** | **кг** | **ккал/ч** | **ккал/ч** |
| G46C TS | Премиум | Touch screen | Полный разбор | 1000 | 1420 | 2340 | 700 | 40000 | 25000 |
| G46C TS2M | | Touch screen | 2 модуля | | | | | | |
| G46C TSTA | | Touch screen | Полная сборка | | | | | | |
| G46C DP | | Цифровая | Полный разбор | | | | | | |
| G46C DP2M | | Цифровая | 2 модуля | | | | | | |
| G46C DPTA | | Цифровая | Полная сборка | | | | | | |
| G46C EMP | Базовая | Электромеханическая | Полный разбор | | | | | | |
| G46C EMPTA | | Электромеханическая | Полная сборка | | | | | | |

| МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 60X80)<br>ЭЛЕКТРИЧЕСКИЕ | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Модель** | **Версия** | **Панель управления** | **Тип сборки** | **Габариты** | | | **Вес** | **Мощность** | **Среднее потребление** |
| | | | | **д** | **ш** | **в** | | | |
| | | | | **мм** | **мм** | **мм** | **кг** | **кВт** | **кВт/ч** |
| G68E TS КРЮК | Премиум | Touch screen | Полный разбор | 1430 | 1970 | 2540 | 1200 | 49+2,3 | 36 |
| G68E TST ПЛАТФОРМА | | Touch screen | | | | | 1272 | | |
| G68E DP КРЮК | | Цифровая | | | | | 1200 | | |
| G68E DPT ПЛАТФОРМА | | Цифровая | | | | | 1272 | | |
| G68E EMP КРЮК | Базовая | Электромеханическая | | | | | 1200 | | |
| G68E EMPT ПЛАТФОРМА | | Электромеханическая | | | | | 1272 | | |

| МОДЕЛЬНЫЙ РЯД СЕРИИ G (РАЗМЕР ЛИСТОВ 60X80)<br>ГАЗОВЫЕ | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Модель** | **Версия** | **Панель управления** | **Тип сборки** | **Габариты** | | | **Вес** | **Мощность** | **Среднее потребление** |
| | | | | **д** | **ш** | **в** | | | |
| | | | | **мм** | **мм** | **мм** | **кг** | **ккал/ч** | **ккал/ч** |
| G68C TS КРЮК | Премиум | Touch screen | Полный разбор | 1430 | 1970 | 2540 | 1255 | 40000 | 25000 |
| G68C TST ПЛАТФОРМА | | Touch screen | | | | | 1327 | | |
| G68C DP КРЮК | | Цифровая | | | | | 1255 | | |
| G68C DPT ПЛАТФОРМА | | Цифровая | | | | | 1327 | | |
| G68C EMP КРЮК | Базовая | Электромеханическая | | | | | 1255 | | |
| G68C EMPT ПЛАТФОРМА | | Электромеханическая | | | | | 1327 | | |

EN

# ROTARY RACK OVENS

## G SERIES




Compact dimensions, solid structure, refined design and great functionality at the same time. Apach Bakery Line
G series rotary ovens are highly reliable products that offer wide warranties of quality to the most exigent users.

## STANDARD EQUIPMENT

- TS version: TOUCH SCREEN control panel with 7" TFT, 99 multiphase programs with products' images, programmable steam damper
- DP version: digital control panel with new generation multifunction-rotary swith for quick selection of the different controls, LCD screen, 30 storable programs, 2-speed baking ventilation
- EMP version: : electromechanical control panel
- Hook turning system geared by motor-reducer with safety clutch
- 2-speed baking ventilation (ideal for delicate pastry or soft bread)
- Impact-free protected silicon joints mounted on the door
- Hood with extractor
- Stainless steel double glazed "TOTAL VISION" door equipped with 180° opening system
- Powerful steam generator designed and tested for massive steam production with very fast recovery times
- Highly refractory combustion chamber that can be totally inspected, with excellent performances, covered by a 3-years warranty
- Fast-recovering powerful steam generator
- Access to the burner or resistances from the left side
- Available in electric or fired version (for gas, LPG or gasoil/diesel burner)
- Rear heat exchanger including stainless steel highly-refractory firebox with left-side access for maintenance
- Heavy duty insulation with pre-compressed rockwool panels
- Practical upper rotation hook allowing the rack's movement and the oven's cleaning
- Stainless steel interior/exterior

## OPTIONS / ACCESSORIES

- Turntable (except G46 range)
- Automatic rack lifter (except G46 range)
- Access to the burner or resistances from the right side
- Extra powered heating elements for electric ovens - intensive use or frozen bread
- Display on the hood showing baking time/chamber temperature

## ADVANTAGES

- Solid structure
- Refined design and functional
- Optimal energy consumption
- A complete set of options required for any type of product
- Modern and technological design

| EQUIPMENT | | | |
|---|---|---|---|
| EMP | DP | TS | |
| ✗ | ✗ | ✓ | TOUCH SCREEN control panel with 7" TFT, 99 multiphase programs with products' images, programmable steam damper |
| ✗ | ✓ | ✗ | Digital control panel with new generation multifunction-rotary swith for quick selection of different controls, LCD screen, 30 storable programs |
| ✓ | ✗ | ✗ | Electromechanical control panel |
| ✓ | ✓ | ✓ | 2-speed baking ventilation (ideal for delicate pastry or soft bread) |
| ✓ | ✓ | ✓ | Hook turning system geared by motor-reducer with safety clutch |
| ✓ | ✓ | ✓ | Hood equipped with extractor |
| ✓ | ✓ | ✓ | Stainless steel double glazed door equipped with 180° opening system |
| ✓ | ✓ | ✓ | Heavy duty insulation with pre-compressed rockwool panels |
| ✓ | ✓ | ✓ | Stainless steel interior/exterior |
| ✓ | ✓ | ✓ | Powerful steam generator (protected by a patent), designed and tested for massive steam production with very short recovery times |
| ✗ | ✓ | ✓ | Automatic damper for steam removal |
| ✓ | ✗ | ✗ | Manual damper for steam removal |
| ✓ | ✓ | ✓ | External electrical cabinet (positioned at the back, top or wall) |
| ✓ | ✓ | ✓ | The oven is delivered disassembled (on request in 2 or 3 modules or fully assembled) |

✓ Default
✗ Option

THE LINEUP G SERIES (TRAYS 40X60)
ELECTRIC

| Model | Version | Control panel | Assembly | Dimensions | | | Weight | Power | Average consumption |
|---|---|---|---|---|---|---|---|---|---|
| | | | | L | W | H | | | |
| | | | | mm | mm | mm | kg | kW | kW/h |
| G46E TS | Premium | Touch screen | Unassembled | 1000 | 1420 | 2340 | 650 | 24+1,5 | 18 |
| G46E TS2M | | Touch screen | 2 modules | | | | | | |
| G46E TSTA | | Touch screen | Total assembled | | | | | | |
| G46E DP | | Digital | Unassembled | | | | | | |
| G46E DP2M | | Digital | 2 modules | | | | | | |
| G46E DPTA | | Digital | Total assembled | | | | | | |
| G46E EMP | Basic | Electromechanical | Unassembled | | | | | | |
| G46E EMPTA | | Electromechanical | Total assembled | | | | | | |

| THE LINEUP G SERIES (TRAYS 40X60)<br>BURNER | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Model** | **Version** | **Control panel** | **Assembly** | **Dimensions** | | | **Weight** | **Power** | **Average consumption** |
| | | | | **L** | **W** | **H** | | | |
| | | | | **mm** | **mm** | **mm** | **kg** | **Kcal/h** | **Kcal/h** |
| G46C TS | Premium | Touch screen | Unassembled | 1000 | 1420 | 2340 | 700 | 40000 | 25000 |
| G46C TS2M | | Touch screen | 2 modules | | | | | | |
| G46C TSTA | | Touch screen | Total assembled | | | | | | |
| G46C DP | | Digital | Unassembled | | | | | | |
| G46C DP2M | | Digital | 2 modules | | | | | | |
| G46C DPTA | | Digital | Total assembled | | | | | | |
| G46C EMP | Basic | Electromechanical | Unassembled | | | | | | |
| G46C EMPTA | | Electromechanical | Total assembled | | | | | | |

| THE LINEUP G SERIES (TRAYS 60X80)<br>ELECTRIC | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Model** | **Version** | **Control panel** | **Assembly** | **Dimensions** | | | **Weight** | **Power** | **Average consumption** |
| | | | | **L** | **W** | **H** | | | |
| | | | | **mm** | **mm** | **mm** | **kg** | **kW** | **kW/h** |
| G68E TS HOOK | Premium | Touch screen | Unassembled | 1430 | 1970 | 2540 | 1200 | 49+2,3 | 36 |
| G68E TST TURNTABLE | | Touch screen | | | | | 1272 | | |
| G68E DP HOOK | | Digital | | | | | 1200 | | |
| G68E DPT TURNTABLE | | Digital | | | | | 1272 | | |
| G68E EMP HOOK | Basic | Electromechanical | | | | | 1200 | | |
| G68E EMPT TURNTABLE | | Electromechanical | | | | | 1272 | | |

| THE LINEUP G SERIES (TRAYS 60X80)<br>BURNER | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| **Model** | **Version** | **Control panel** | **Assembly** | **Dimensions** | | | **Weight** | **Power** | **Average consumption** |
| | | | | **L** | **W** | **H** | | | |
| | | | | **mm** | **mm** | **mm** | **kg** | **Kcal/h** | **Kcal/h** |
| G68C TS HOOK | Premium | Touch screen | Unassembled | 1430 | 1970 | 2540 | 1255 | 40000 | 25000 |
| G68C TST TURNTABLE | | Touch screen | | | | | 1327 | | |
| G68E DP HOOK | | Digital | | | | | 1255 | | |
| G68E DPT TURNTABLE | | Digital | | | | | 1327 | | |
| G68E EMP HOOK | Basic | Electromechanical | | | | | 1255 | | |
| G68E EMPT TURNTABLE | | Electromechanical | | | | | 1327 | | |