IT-EN



one

EGRO

SWISS COFFEE TECHNOLOGY

EGRO ONE.
COMPATTA E PERFORMANTE

Egro ONE integra stile e funzionalità, senza rinunciare alla qualità in tazza. E' la soluzione ideale per diverse tipologie di location, come hotel, catene fast-food, convenience store e ristoranti.

INTERFACCE USER-FRIENDLY

Interfacce utente versatili e funzionali facilitano il lavoro quotidiano del barista.
ONE è disponibile in tre differenti configurazioni:

Keypad – fino a 16 prodotti selezionabili
La pulsantiera è composta da 10 semplici tasti per la selezione di 5, 9 o 16 diverse bevande con grafica personalizzabile dall'utente.
Touch Standard – fino a 48 prodotti selezionabili
Il display grafico a colori guida il barista nella scelta delle bevande ciascuna contrassegnata da una propria icona intuitiva. ONE offre la possibilità di caricare screensaver personalizzati, immagini e video.
Touch Multi Drink Software - oltre 1000 prodotti configurabili
Attraverso diversi passaggi progressivi, l'utente può comporre la propria bevanda scegliendo dosaggio, miscela, tipologia di latte e prodotti in polvere. Un nuovo approccio rapido e veloce particolarmente adatto alle soluzioni self-service.

PREMIUM QUALITY DRINKS

CAFFÈ

Risultato in tazza costante e di estrema qualità grazie a:
- Gruppo erogatore da 18 grammi in acciaio inossidabile
- DURA BREW sistema brevettato di chiusura ermetica che richiede minori interventi di manutenzione e riduce i costi complessivi di utilizzo della macchina.
- Becco facilmente scomponibile, rimuovibile e lavabile
- Macinatura ad impulsi e macine in acciaio inossidabile per una perfetta costanza e precisione della dose di macinato

LATTE

La versione più evoluta Top-Milk XP garantisce versatilità e precisione grazie a:
- Regolazione via software di parametri quali temperatura e tessitura delle bevande
- Sistema brevettato MLR (Milk Line Rinsing) che miscela acqua fredda e aria durante la fase di risciacquo per evitare sprechi di energia elettrica
- Frigorifero KS9 da 6,5 litri con display esterno e sensore capacitivo per il monitoraggio del livello del latte
- Opzione Multi-Milk Selection che consente l'uso di due differenti tipologie di latte
- Frigorifero FUM da 4 litri posizionato sotto la macchina per una maggiore ottimizzazione degli spazi dotato di sensore brevettato per un controllo preciso e puntuale
- Predisposizione per l'utilizzo di svariate unità refrigeranti sotto il bancone del bar



POLVERI

Il Modulo Polveri permette l'utilizzo di una molteplicità di preparati dai gusti più disparati. Si tratta di un dispositivo esterno posizionato sul lato destro della macchina e costituito da due tramogge indipendenti.

ACQUA E VAPORE

Una gestione ottimale dei servizi aggiuntivi con:
4-TEA prevede diversi gradi di calore dell'acqua e dosaggi programmabili per tè e infusi di qualità
iSteam permette di scaldare e montare il latte in maniera automatica.
iSteam Plus (solo per ONE Pure Coffee) migliora le performance della lancia vapore per scaldare il latte. Appositamente progettata per location che hanno un elevato consumo di bevande a base di latte caldo.
Cool Touch lancia vapore isolata termicamente per operare in pieno comfort e sicurezza

EGRO ONE.
COMPACT AND POWERFUL

Egro ONE combines style with high quality functionality. This is the essence of Egro ONE, ideal partner for different types of locations, such as hotel, chains, convenience store and restaurant.

USER-FRIENDLY INTERFACES

Easy to use interfaces to help the barista in his work.
Egro ONE is available in three different configurations:
Keypad – up to 16 products
The Keypad has a user-friendly 10-key buttons for selecting 5, 9 or 16 drinks with customizable graphics by the user.
Touch Standard – up to 48 products
The full colour graphic display guides the barista through the choice of products, each one with its own attractive intuitive icon. It also offers the option of uploading images or videos and customizing screensavers.



Touch Multi Drink Software – more than 1.000 products configurations
Through different and progressive steps, the user can easily create his beverages selecting cup size, blend of coffee, type of milk and powders. This new approach speeds up selection operations on self-service machines.

PREMIUM QUALITY DRINKS

COFFEE

Highest and consistent quality in the cup thanks to:
- Brewing group in stainless steel with 18 grams brew chamber capacity,
- DURA BREW, a patented hermetic closing system, which requires less maintenance and reduces the overall operating costs of the machine.
- Dispensing spout easily removable, and washable for a perfect hygiene.
- The grind pulses sensor and the quality of the steel burrs ensure perfect coffee dose consistency and precision for the preparation of the programmed beverages.

MILK

Egro ONE Top Milk XP guarantees versatility and precision in delivering milk-based products thanks to:
- Setting by software milk temperatures and textures for each drink
- Patented MLR (Milk Line Rinsing) system makes it possible to set a rapid rinsing phase with the aid of cold water and air, which reduces electricity consumption.
- Space-saving Fridge equipped with a 4-litre tank positioned under the machine and equipped with a patented milk level sensor for a precise monitoring of the milk level.
- Possibility to set any kind of refrigerators under the counter

POWDERS

The Powder Module can deliver an increasingly varied and exhaustive choice of beverages. It is an external device positioned on the right hand side of the machine and consists of two independent hoppers.

WATER AND STEAM

High performance with additional services:
4-Tea has different temperatures and programmable doses for tea essences and infusions.
The **iSteam** wand allows milk to be heated and frothed automatically.
iSteam Plus (only for ONE Pure Coffee) improves the performances of steaming hot milk. Designed for locations that have a very high consumption of hot milk beverages.
Cool Touch wand thermally insulated to work safely and easy to clean.

ONE PURE-COFFEE



DATI TECNICI / TECHNICAL INFO

	ONE PURE COFFEE
Dimensioni (L×P×A) - **Dimensions** (W×D×H)	300×570×770 mm / 11.8×22.4×30.3 in
Voltaggio - Voltage	1N ~220V-240V / 2N ~380-415V
Potenza (kW) - Power (kW)	3.6 kW / 6 kW
Peso - Weight	57 kg / 125.7 lb

CARATTERISTICHE TECNICHE

PANNELLO OPERATIVO
• Keypad, 16 pulsanti
• Touch, standard 48 Prodotti
• Touch, Multi Drink Software

ACQUA CALDA
• Uscita acqua calda esterna - lato destro
• Uscita acqua calda centrale - in uscita caffè

OPZIONI CAFFE
Secondo macinino, Self Adjusting Grinder per 1 o 2 macinini, Bypass tazza doppia, Bypass tazza singola, Dispositivo di espulsione fondi caffè

OPZIONI VAPORE
Lancia Vapore C-Lever, Lancia Vapore C-Lever con Cool Touch, iSteam, iSteam PLUS - 3 valvole

ACCESSORI
Scaldatazze, Modulo polveri, Kit per trolley, Sistemi di pagamento

VARIE
Opzione Self *(kit serrature e posizionatore tazza)*, Kit serrature, Automatic Spout

TECHNICAL FEATURES

OPERATING PANEL
• Keypad, 16 buttons
• Touch, standard 48 Products
• Touch, Multi Drink Software

HOT-WATER
• External Hot Water outlet - right side
• Central Hot Water outlet - in coffee outlet

COFFEE OPTIONS
Second grinder, Self Adjusting Grinder for 1 or 2 grinders, Bypass Dual Cup, Bypass Single Cup, Ejection device for waste coffee drawer

STEAM OPTIONS
C-Lever Steam wand, C-Lever Steam wand with Cool Touch, iSteam, iSteam PLUS - 3 valves

ACCESSORIES
Cup Warmer, Powder Module, Built-in Trolley Kit, Payment Systems

MISCELLANEOUS
Option Self *(lock package dnd cup stopper pins)*, Lock Package, Automatic Spout

ONE QUICK-MILK



DATI TECNICI / TECHNICAL INFO

	ONE QUICK-MILK
Dimensioni (L×P×A) - **Dimensions** (W×D×H)	300×570×770 mm / 11.8×22.4×30.3 in
Voltaggio - Voltage	1N ~220V-240V / 2N ~380-415V
Potenza (kW) - Power (kW)	3.6 kW / 6 kW
Peso - Weight	57 kg / 125.7 lb

CARATTERISTICHE TECNICHE

PANNELLO OPERATIVO
• Keypad, 16 pulsanti
• Touch, standard 48 Prodotti
• Touch, Multi Drink Software

ACQUA CALDA
• Uscita acqua calda esterna - lato destro
• Uscita acqua calda centrale - in uscita caffè

OPZIONI CAFFE
Secondo macinino, Self Adjusting Grinder per 1 o 2 macinini, Bypass tazza doppia, Bypass tazza singola, Dispositivo di espulsione fondi caffè

OPZIONI VAPORE
Lancia Vapore C-Lever, Lancia Vapore C-Lever con Cool Touch, iSteam

OPZIONI SISTEMA LATTE
Cool Box 6.5, Quick-Milk Fridge, FUM Fridge under machine

ACCESSORI
Scaldatazze, Modulo polveri, Kit per trolley, Sistemi di pagamento

VARIE
Opzione Self *(kit serrature e posizionatore tazza)*, Kit serrature, Automatic Spout

TECHNICAL FEATURES

OPERATING PANEL
• Keypad, 16 buttons
• Touch, standard 48 Products
• Touch, Multi Drink Software

HOT-WATER
• External Hot Water outlet - right side
• Central Hot Water outlet - in coffee outlet

COFFEE OPTIONS
Second grinder, Self Adjusting Grinder for 1 or 2 grinders, Bypass Dual Cup, Bypass Single Cup, Ejection device for waste coffee drawer

STEAM OPTIONS
C-Lever Steam wand, C-Lever Steam wand with Cool Touch, iSteam

MILK SYSTEM OPTIONS
Cool Box 6.5, Quick-Milk Fridge, FUM Fridge under machine

ACCESSORIES
Cup Warmer, Powder Module, Built-in Trolley Kit, Payment Systems

MISCELLANEOUS
Option Self *(lock package and cup stopper pins)*, Lock Package, Automatic Spout

ONE TOP-MILK XP



DATI TECNICI / TECHNICAL INFO

	TOP-MILK XP
Dimensioni (L×P×A) - **Dimensions** (W×D×H)	300×570×770 mm / 11.8×22.4×30.3 in
Voltaggio - Voltage	1N ~220V-240V / 2N ~380-415V
Potenza (kW) - Power (kW)	3.6 kW / 6 kW
Peso - Weight	57 kg / 125.7 lb

CARATTERISTICHE TECNICHE

PANNELLO OPERATIVO
• Keypad, 16 pulsanti
• Touch, standard 48 Prodotti
• Touch, Multi Drink Software

ACQUA CALDA
• Uscita acqua calda esterna - lato destro
• Uscita acqua calda centrale - in uscita caffè

SISTEMA LATTE
• Frigorifero laterale sinistro, KS9
(opzioni: estensione sottobancone, selezione multi-milk, sensore livello 1 tipo latte, sensore livello 2 tipi latte)
• Frigorifero laterale sinistro, KS9, Cold Milk Foam *(opzioni: sensore livello 1 tipo latte)*
• FUM Fridge under machine
• Kit modulo pompa *(opzioni: 1 tipo latte - 1 macchina, 2 tipi latte - 1 macchina, 1 tipo latte - 2 macchine, 2 tipi latte - 2 macchine)*

OPZIONI CAFFE
Secondo macinino, Self Adjusting Grinder per 1 o 2 macinini, Bypass tazza doppia, Bypass tazza singola, Dispositivo di espulsione fondi caffè

OPZIONI VAPORE
Lancia Vapore C-Lever, Lancia Vapore C-Lever con Cool Touch, iSteam

ACCESSORI
Scaldatazze, Modulo polveri, Kit per trolley, Sistemi di pagamento

VARIE
Opzione Self *(kit serrature e posizionatore tazza)*, Kit serrature, Automatic Spout

TECHNICAL FEATURES

OPERATING PANEL
• Keypad, 16 buttons
• Touch, standard 48 Products
• Touch, Multi Drink Software

HOT-WATER
• External Hot Water outlet - right side
• Central Hot Water outlet - in coffee outlet

MILK SYSTEM
• Side Fridge left, KS9
(options: extension under counter fridge, multi-milk selection, Milk 1 type level sensor, Milk 2 type level sensor)
• Side Fridge left, KS9 , Cold Milk Foam *(options: Milk 1 type level sensor)*
• FUM Fridge under machine
• Pump module unit *(options: 1 milk - 1 machine, 1 milk - 2 machine, 2 milk - 2 machine)*

COFFEE OPTIONS
Second grinder, Self Adjusting Grinder for 1 or 2 grinders, Bypass Dual Cup, Bypass Single Cup, Ejection device for waste coffee drawer

STEAM OPTIONS
C-Lever Steam wand, C-Lever Steam wand with Cool Touch, iSteam

ACCESSORIES
Cup Warmer, Powder Module, Built-in Trolley Kit, Payment Systems

MISCELLANEOUS
Option Self *(lock package and cup stopper pins)*, Lock Package, Automatic Spout

DATI TECNICI / TECHNICAL INFO

CAPACITÀ EROGAZIONE / DELIVERY CAPACITY (DIN 18873-2 / Single Dose • Double Dose)

	PURE-COFFE	QUICK-MILK
Espresso [tazze/ora] **Espresso** [cups/hour]	125 • 205	125 • 205
Cappuccino [tazze/ora] **Cappuccino** [cups/hour]		120 • 160
Caffè lungo [tazze/ora] **Cafe Creme** [cups/hour]	109 • 140	109 • 140
Acqua calda [tazze/ora] **Hot Water** [cups/hour]	186	186
Produzione ottimale giornaliera [max tazze/gg] **Recommended daily output** [max cups/day]	200	200
Dispersione di energia al giorno [kWh] **Energy loss per day** [kWh]	1,772	1,772

SCALDATAZZE / CUP WARMER

Dimensioni (L×P×A) - **Dimensions** (W×D×H)	300×455×580 mm / 11.8×17.9×22.8 in
Voltaggio - Voltage	1N ~230V 50/60Hz
Potenza (kW) - Power (kW)	0.42 kW
Peso - Weight	14 kg / 30.1 lb

MODULO POLVERI / POWDER MODULE

Dimensioni (L×P×A) - **Dimensions** (W×D×H)	160×470×770 mm / 6.3×18.5×30.3 in
Voltaggio - Voltage	1N ~230V 50/60Hz / 1N ~120V 60Hz
Potenza (kW) - Power (kW)	0.10 kW
Peso - Weight	13 kg / 28.1 lb

FRIGORIFERO KS9 / FRIDGE KS9

Dimensioni (L×P×A) - **Dimensions** (W×D×H)	300×455×580 mm / 11.8×17.9×22.8 in
Voltaggio - Voltage	1N ~230V 50/60Hz / 120V 60Hz
Potenza (kW) - Power (kW)	0.10 kW
Peso - Weight	29 kg / 63.9 lb
Capacità - Capacity	6.5 l

FRIDGE UNDER MACHINE (FUM)

Dimensioni (L×P×A) - **Dimensions** (W×D×H)	315×600×203 mm / 12.4×23.6×8.0 in
Voltaggio - Voltage	1N ~220V-230V 50/60Hz / 1N ~115V 60Hz
Potenza (kW) - Power (kW)	0.08 kW kW
Peso - Weight	18.5 kg / 40.0 lb
Capacità - Capacity	4 l

QUICK-MILK FRIDGE

Dimensioni (L×P×A) - **Dimensions** (W×D×H)	230×460×340 mm / 9.0×18.1×13.4 in
Voltaggio - Voltage	1N ~230V 50/60Hz / 1N ~120V 60Hz
Potenza (kW) - Power (kW)	0.10 kW
Peso - Weight	14 kg / 30.1 lb
Capacità - Capacity	4 l

COOL BOX 6.5

Dimensioni (L×P×A) - **Dimensions** (W×D×H)	284×361×440 mm / 11.8×14.2×17.3 in
Voltaggio - Voltage	1N ~230V 50/60Hz
Potenza (kW) - Power (kW)	0.10 kW
Peso - Weight	7 kg / 15,7 lb
Capacità - Capacity	6.5 l

CONTATTI / CONTACTS

HEADQUARTERS, PRODUCTION PLANT AND R&D CENTERS

Rancilio Group S.p.A. con socio unico
Viale della Repubblica 40
20015 Villastanza di Parabiago (MI) - Italy
Ph. +39 0331 408200
Fax +39 0331 551437
info@ranciliogroup.com

Egro Suisse AG
Bahnhofstrasse 66
5605 Dottikon - Switzerland
Ph. +41 (0)56 616 95 95
Fax +41 (0)56 616 95 97
info-ch@ranciliogroup.com

WORLDWIDE BRANCH LOCATIONS

Spain
Rancilio Group España, S.A.
Gran Vía de Carlos III, 84 3ª-Edificio Trade
08028 Barcelona - Spain
Ph. +34 902 884 275
Ph. +34 934 923 414
Fax +34 934 965 701
info-es@ranciliogroup.com

Portugal
Rancilio Group Portugal Lda
Rua José Vicente Gonçalves n°14-Armaz.-2
Parque Industrial do Seixal
2840-048 Aldeia de Paio Pires-Seixal
Lisboa - Portugal
Ph. +351 21 493 52 58

Rua Nova Urbanização do Cavaco 76
4470-264 Maia - Porto - Portugal
Ph. + 351 22 010 14 19
Fax + 351 22 010 14 20
info-pt@ranciliogroup.com

Germany
Rancilio Group Deutschland GmbH
Isenburg - Park
Schleussnerstr. 90
63263 Neu-Isenburg - Germany
Ph. +49 (0)6102 799030
info-de@ranciliogroup.com

Switzerland
Egro Suisse AG
Bahnhofstrasse 66
5605 Dottikon - Switzerland
Ph. +41 (0)56 616 95 95
Fax +41 (0)56 616 95 97
www.egrosuisse.ch

USA/Canada
Rancilio Group North America Inc.
1340 Internationale Parkway / Suite 200
Woodridge, IL 60517 - U.S.A.
Ph. +1 630 914 7900
Fax +1 630 914 7901
Toll Free: +1 877 726 2454
www.ranciliogroupna.com

www.ranciliogroup.com

www.facebook.com/RancilioGroup

Rancilio Group Channel

https://instagram.com/ranciliogroup/

RANCILIO GROUP

an Ali Group Company

GROUP
The Spirit of Excellence

IT - EN
COD. 90 011 199 | 04 -2017