ХЛЕБОРЕЗКИ
СЕРИИ G42



Настольная модель G42 с ручным режимом нарезки. Благодаря компактным размерам модель G42 может использоваться в магазинах, на небольших производствах и в ресторанах.

СТАНДАРТНОЕ ОБОРУДОВАНИЕ

- Изготовлены из стали с окрашиванием в белый цвет
- Толщина нарезки варьируется от 9 до 20 мм
- Ручной режим нарезки
- Обслуживание спереди
- Соответствуют последним нормам безопасности ЕС

ОПЦИИ / АКСЕССУАРЫ

- Роздув пакетов для хлеборезок
- Рабочий стол на колесах для настольной хлеборезки
- Система смазки

МОДЕЛЬНЫЙ РЯД СЕРИИ G42

Модель	Номинальная ширина нарезки	MAX высота хлеба	Толщина нарезки	Вес	Мощность	Габариты		
						Длина	Ширина	Высота
	мм	мм	мм	кг	кВт	мм	мм	мм
G42 9мм	420	180	9	98	0,55	650	658	759
G42 10мм	420	180	10	98	0,55	650	658	759
G42 11мм	420	180	11	98	0,55	650	658	759
G42 12мм	420	180	12	98	0,55	650	658	759
G42 13мм	420	180	13	98	0,55	650	658	759
G42 14мм	420	180	14	98	0,55	650	658	759
G42 15мм	420	180	15	98	0,55	650	658	759
G42 16мм	420	180	16	98	0,55	650	658	759
G42 17мм	420	180	17	98	0,55	650	658	759
G42 18мм	420	180	18	98	0,55	650	658	759
G42 19мм	420	180	19	98	0,55	650	658	759
G42 20мм	420	180	20	98	0,55	650	658	759

ХЛЕБОРЕЗКИ
СЕРИИ G42



Counter-top manual model for general use. Thanks to its compact size, the G42 model is suitable for behind-the-counter use in shops, small laboratories and restaurants.

STANDART EQUIPMENT

- Steel powder painted body
- Slice thickness ranges from 9 to 20 mm
- Manual
- Front loading
- With compliance to the latest European safety standards

OPTIONS / ACESSORIES

- Forced air bag blower for packaging sliced or whole bread
- The base with wheels for the counter-top slicer
- Oiling system

THE LINEUP G42 SERIES								
Model	Nominal width cut	Loaf MAX height	Blade pitches	Weight	Power	Dimensions		
						Length	Width	Height
	mm	mm	mm	kg	kW	mm	mm	mm
G42 9mm	420	180	9	98	0,55	650	658	759
G42 10mm	420	180	10	98	0,55	650	658	759
G42 11mm	420	180	11	98	0,55	650	658	759
G42 12mm	420	180	12	98	0,55	650	658	759
G42 13mm	420	180	13	98	0,55	650	658	759
G42 14mm	420	180	14	98	0,55	650	658	759
G42 15mm	420	180	15	98	0,55	650	658	759
G42 16mm	420	180	16	98	0,55	650	658	759
G42 17mm	420	180	17	98	0,55	650	658	759
G42 18mm	420	180	18	98	0,55	650	658	759
G42 19mm	420	180	19	98	0,55	650	658	759
G42 20mm	420	180	20	98	0,55	650	658	759