


Ice Cube

C 150

BREMA Ice Makers

Modular ice maker - Sprayer system
Daily production up to 160 kg



▶ Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

▶ Performances

Air temperature	Water temperature 7° C	45° F	15° C	60° F	21° C	70° F
10° C	160 kg					
50° F		353 lbs				
21° C			155 kg			
70° F				342 lbs		
32° C					132 kg	
90° F						291 lbs

▶ Connections

All measures are referred to the down-left corner (L-H-Ø)

① Water in.: 126 mm / 4 15/16" - 284 mm / 11 3/16" - 3/4"
② Cond. water in.: 94 mm / 3 11/16" - 234 mm / 9 3/16" - 3/4"
③ Water out.: 69 mm / 2 11/16" - 297 mm / 11 11/16" - 24 mm / 15/16"
④ Electrical connections: 140 mm / 5 8/16" - 355 mm / 14"

▶ Technical information

Production in 24h	155 kg / 342 lbs
Cooling system	A - W
Kind of cube	A-18g, C-33g, D-13g, E-42g, B-60g
Refrigerant	R404A - R452A
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	1400 W
Fuse	16 A
Finish	AISI 304 stainless steel, scotch brite

Water consumption	A: 2,6 l/kg - 31,1 gal/100 lbs
	W: 13 l/kg - 155,8 gal/100 lbs
Sizes (L-P-H mm)	862 - 555 - 720
(L-P-H in)	33 15/16 - 21 14/16 - 28 6/16
Sizes with pack (L-P-H mm)	910 - 605 - 955
(L-P-H in)	35 13/16 - 23 13/16 - 37 10/16
Net weight	118 kg / 260 lbs
Gross weight	128 kg / 282 lbs

All the technical information need to be considered at the following conditions:
Standard Cube (18 g)
Ambient temperature +21° C
Water temperature +15° C
Average power consumption at +43° C (standard voltage)
Refrigerant R404A

Models and specifications are subject to change without notice

Rev. 03 - Issued May 2018

BREMA Ice Makers
www.bremaice.it
info@bremaice.it

Bim + Data download